



Model: MOSS-D1004Q

**Features:**

- 10" Vehicle reversing Quad HD Digital LCD monitor
- Resolution: 1024(W) \*R.G.B\* 600(H)
- Wide screen display: 16:9
- PAL / NTSC auto-switching
- 4 ways video input, 1 way audio input, with AV-IN input
- 4 ways video display for reversing (front, rear, left, right)
- Built-in Quad Mode
- Full image/ 2 images/ 3images/ 4 images adjustable
- 4pin connector
- Built-in display delay function when reversing with 2~5 seconds adjustable
- Image can be adjustable up / down
- Built-in speaker
- Multi-language display: English, Chinese, Italian, Germany, French
- View angle range: (left/right) 65° (top) 40° (down) 15°
- Automatically adjust light sensor
- IR Remote controller
- OSD menu display
- U-Shape bracket
- Sunshade design around
- Dimension: 285(L)\*184(W)\*34(H) mm
- DC9~24V wide voltage

## Specifications:

|                                 |   |
|---------------------------------|---|
| Model No.                       | <b>MOSS-D1004Q</b>                                      |
| Screen Size                     | 10-inch wide screen display                             |
| Display Resolution              | 1240(W) *R.G.B* 600(H) dots                             |
| Screen                          | TFT LCD Screen  |
| LCD Profile Ratio               | 16:9  |
| The display of imitate quantity | OSD display   |
| Adjustment Items                | Brightness, Contrast, Color, Volume, Languages, Up/down |
| Color System                    | PAL / NTSC system auto-switching                        |
| Video Input                     | 1VP-P 75Ω (4 ways)                                      |
| Audio Input                     | 1 way   |
| Built-in Quad inside            | Yes   |
| View angel range                | (left/right)65° (top)40° (down)15°                      |
| Built-in Speaker                | Yes   |
| Multi-Languages                 | English, Chinese, Germany, Italian, French, Spanish     |
| Connectors                      | 4-Pin Connector   |
| Bracket                         | Includes "U" Shape Bracket                              |
| Temp. range                     | Negative 68 degrees F to 158 degrees F                  |
| Power supply                    | DC9~24V wide voltage                                    |
| Power Consumption               | 5W  |
| Dimension(mm)                   | 285(L)*184(W)*34(H)mm                                   |