



MOSS-211M-M



Housing No.: MOSS-211M-M

Features:

- Car rear view camera
- CMOS,MT9V136
- Signal system: PAL / NTSC
- Usable illumination:1 Lux.at F1.2
- Outstanding signal to noise ratio better than 48dB
- Support normal / Mirror switching
- Support reversing reference line
- IP68 Waterproof function design
- 170° wide view angle
- Casing color: black
- Casing material: zinc alloy
- RCA connector
- DC12V

Specifications:

Model No.	MOSS-211M-M	MOSS-211M-M-MT9V136
Pick up Device	1/4" Color CMOS	1/3" Color CMOS
Signal Formal	PAL / NTSC (color)	
Effective Pixels	P:512(H)*582(V); N:512(H)*492(V)	P:512(H)*582(V); N:512(H)*492(V)
Horizontal Resolution	420TVL	420TVL
Usable illumination	0 Lux (Infrared LEDs on,at F1.2)	
Infrared LEDs	N/A	
IR working distance	N/A	
Infrared Wavelength	N/A	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec 2:1Interlace	
Synchronization	Internal sync.	
S.N Ratio	≥48dB(AGC off)	
Auto Gain Control	Auto	
White Balance	Auto	
Electronic Shutter	Auto: PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Video Output	1Vp-p,75ohm Composite, RCA connector	
Audio Output	N/A	
Mirror image	Support Normal / mirror switching	
Parking line	Support reversing reference line (optional)	
Gamma Ratio	≥0.45	
View angle for lens	170°	
Waterproof function	IP68	
Power Supply	DC12V	
Power Consumption	120mA	
Temp. range	negative 68 degrees F to 158 degrees F	
Casing color	black	
Casing material	Zinc alloy	

G.P.S TRACKING, FLEET MANAGEMENT & MOBILE SURVEILLANCE SYSTEMS

636 Hempstead Turnpike, Franklin Square, NY 11010 P: 516.489.2350 F: 516.489.8430 www.movinggps.com