MOSS-701-235-UM



Features:

- Metal-cased mini housing with standard fixed lens.
- Available in black finish.
- Low power consumption.
- Easy installation on ceiling or wall, surface or flush mount.
- Audio output.

Cautions:

- 1. Please do not touch the lens with your fingers. If necessary, use a soft cloth moistened with alcohol to wipe away the dust.
- 2. Please avoid placing or using the camera under direct sunlight.
- 3. Please ensure that the input voltage range is within the specifications.
- 4. Do not attempt to service the camera by yourself. Please refer all services to qualified dealers.

Operation procedures:

- 1. Attach the mounting bracket (4) to surface as required. Use the supplied screws to fix camera (5) in position ~ a firm mounting surface is essential for a stable installation.
- 2. Connect the s-video cable to system.
- 3. Adjust camera position by loosening the fixed screw (3). Adjust the focus sharpness of the lens (1) by loosening the focus-lock screw (2).
- 4. Re-tighten the all fixed screws.

Packing list:

Camera	1
Instruction manual	.1
Adhesive EPE type	. 1
Mounting screws	2

Model	MOSS-701-235-UM
Pick up Device	2090+1/3" Color Sony 811 CCD
TV System	NTSC
Effective Pixel Array	976H x 582V
Horizontal Resolution	700TVL
Sensitivity	0 Lux (LED On)
Scanning System	2:1 Interlace
Synchronization	Internal
Infrared Spectrum	850nm
Infrared LED	5 LEDs with SMD type
IR range	1.5 M
S/N Ratio	50 dB, (AGC Off)
Audio	Available
Switchable IR filter	No
Auto Gain Control	Auto
White Balance	Auto
Electronic Shutter	Auto
Back Light Compensation	Auto
Video Output	1 Vp-p, 75 Ω Composite
Gamma Ratio	0.45
Lens	Waterproof f2.35mm fixed iris
Lens Angle (D)	145°
Pan Adjusting	+/-30 Degree
Tilt Adjusting	0-90 Degree
Power Supply	12V DC ±10%
Power Consumption	130mA
Dimensions	32.2(L) x 42.6(H) x 29.5 (W) mm
Net Weight	51 g
Weatherproof	N/A
Operating Temperature	-20° C to +50° C