



MOSS-07UR



Housing No.: MOSS-07UR

Features:

- Bus –watch vandalproof & waterproof CCTV IR camera
- 1/3" Color Sony SuperHAD II low Lux CCD
- Resolution: 540TVL,600TVL
- Next Chip DSP
- Signal system: PAL / NTSC
- Usable illumination:0 Lux (Infrared LEDs on,at F1.2)
- Outstanding signal to noise ratio better than 48dB or 54dB
- IP67 Waterproof function design
- 95° wide view angle /3.6mm fixed lens (120° /2.8mm fixed lens wide view angle optional)
- 12pcs/F3 IR LEDs,5m IR working distance
- Casing color: black
- Casing material: Iron
- 4pin connector
- Dimension: (D)54*(H)50mm
- DC12V

Specifications:

Housing No.	MOSS-07UR	
Model No.	MOSS-5407UR	MOSS-6007UR
Pick up Device	1/3" Sony Color CCD	1/3" Sony Color CCD
Signal Formal	PAL / NTSC (color)	
Effective Pixels	P:752(H)*582(V);N:768(H)*494(V)	P:795(H)*596(V);N:811(H)*508(V)
Horizontal Resolution	540TVL	600TVL
Usable illumination	0 Lux (Infrared LEDs on,at F1.2)	
Infrared LEDs	12pcs /F3	
IR working distance	5m	
Infrared Wavelength	850nm (940nm optional)	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec 2:1Interlace	
Synchronization	Internal sync.	
S.N Ratio	≥48dB(AGC off)	≥54dB(AGC off)
Auto Gain Control	Auto	
White Balance	Auto	
Electronic Shutter	Auto: PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Video Output	1Vp-p,75ohm Composite, 4pin connector	
Audio Output	N/A	
Mirror image	Optional	
Gamma Ratio	≥0.45	
View angle for lens	95° /3.6mm fixed lens (120° /2.8mm fixed lens optional)	
Waterproof function	IP67	
Vandalproof function	Available	
Power Supply	DC12V	
Power Consumption	200mA	
Temp. range	Negative 68 degrees F to 158 degrees F	
Casing color	Black	
Casing material	Iron	
Dimension	(D)54*(H)50mm	

G.P.S TRACKING, FLEET MANAGEMENT & MOBILE SURVEILLANCE SYSTEMS

636 Hempstead Turnpike, Franklin Square, NY 11010 P: 516.489.2350 F: 516.489.8430 www.movinongps.com